

Technical data sheet

22-88430 Black BU

Color solutions, pigment dispersion for Epoxy.

22-88430

Product description:

APPLICATION: EPOXY COLORANT

Epoxy colorants are made to serve in a wide variety of epoxy applications. As such, they are best suited for Epoxy Cast, Pultrusions, Filament Winding. Products can also be used in caulk, sealant, and adhesive applications.

Property	Typical value	Analysis method
Density [lb/gal]	9.98	TQ-1-4
Specific Gravity [calculated]	1.20	TQ-1-4
Epoxy Equivalent Weight [EEW]	209	Calculated
Hegman Grind	6.0 to 8.0	TQ-1-20

Product Specification	Lot tolerance	Analysis method
CIELAB DE*	0.00 to 1.00	TQ-1-16
% Strength	95 to 105	TQ-1-16
Density	8.99 to 10.99	TQ-1-4
Hegman Grind	6.0 to 8.0	TQ-1-20
% Color	9.00 to 11.00	Calculated

Limitation of Warranty and Liability

©VibrantZ Technologies. This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.