

## ULS

### Ulrasolve Cleaning Solvent

ULS is a fast-drying solvent specially formulated for the quick and efficient cleaning of electrical equipment. It offers excellent degreasing properties and a fast evaporation rate.

- Excellent degreasing properties; ideal for efficient cleaning of PCBs and electronic equipment
- Also removes flux residues and acrylic conformal coatings; versatile in use
- Fast evaporation rate; efficient cleaning processes
- CO<sub>2</sub> propelled aerosol version available; 20% more active cleaner

<b>Approvals</b>	<b>RoHS-2 Compliant (2011/65/EU):</b>	<b>Yes</b>
<b>Typical Properties</b>	Boiling Point (°C)	>80
	Flash Point (°C)	-20
	Density @ 20°C (g/ml)	0.79
	Inhalation Toxicity (ppm)	300
	Residue on Evaporation (ppm)	1
	Evaporation Rate	16 (ether = 1)

<b>Description</b>	<b>Packaging</b>	<b>Order Code</b>	<b>Shelf Life</b>
<u>Ulrasolve Cleaning Solvent</u>	12ml Pen - Packed in 5's	ULS12P	36 Months
	200ml Aerosol	ULS200D	36 Months
	400ml Aerosol	ULS400D	36 Months
	400ml Aerosol with Brush	ULS400DB	48 Months
	1 Litre Bulk	ULS01L	72 Months
	5 Litre Bulk	ULS05L	72 Months
	25 Litre Bulk	ULS25L	72 Months

#### Directions for Use

ULS is suitable for cleaning PCBs, electronic equipment and components. It removes flux residues as well as offering efficient degreasing properties. In addition, it can be used to remove acrylic conformal coatings. Product contains flammable solvent so do not spray onto live electrical equipment or other sources of ignition. Immerse surface to be cleaned or spray onto surface to excess and allow to evaporate. A brush or foam tipped bud may be used to remove any stubborn deposits. For use on large scale production, ULS may be used in ultrasonic cleaning equipment which must be adapted for use with flammable liquids.

Revision 1: Oct 2013