

## TECHNICAL DATA SHEET

Part#: 7282E

**Cutters - 50° Angulated Head - Blade Length .22" - Short Handle**  
Offers excellent visibility and accessibility with a larger (.22") blade

The 7282E Lazer Line<sup>®</sup> medium angulated/tapered optimum flush cutter with a cutting capacity of .003" - .025" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. This 5.25" tool has a 50° angled tip with a set-screw which prevents over travel while prolonging the life of the tool. It features a ergonomically molded antimicrobial Anti-Static grip (10<sup>10</sup> ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10 <sup>10</sup> ohms/sq
• Shape	Angulated Head
• Type of Cut	Optimum Flush
• Cutting Capacity	.003 - .025"
• Blade Angle	50°
• Blade Length	.22" (5.5mm)
• Body Width	0.42" (10.5mm)
• Body Height	.25" (6.35)
• OAL	5" (125mm)
• Weight (OZ)	3
• UPC	662847009693
• Schedule B	8203.20.60.60
• ECCN	EAR99
• UNSPSC Code	27111511
• Country of Origin	USA
• Group	Angled Head

