



DDSD Station provides a **versatile solution for SMD and high-power applications, excelling in desoldering through-hole components and removing excess solder after SMD removal**. It is ideal for delivering clean, precise results across various soldering tasks.

It provides the **best rework quality** thanks to **JBC Most Efficient Soldering System**, with **Intelligent Heat Management** to **extend tip life and reduce energy consumption**.

Includes:

- **DDE** 2-Tool Control Unit manages up to two tools simultaneously and is fully compatible with 13 different **JBC Tools**, delivering up to 150 W per tool.
- **T245** General Purpose Handle and **DT530** Angled Desoldering Iron.
- T245 works with **C245** Cartridge Range and DT530 with **D530** Tip Range.
- **MSE** Electric Desoldering Module provides exceptional suction power, reaching up to 85% vacuum, ensuring precise and efficient solder removal.

REFERENCES

DDSD-1QB - 120 V

DDSD-2QB - 230 V

DDSD-9QB - 100 V

WEIGHT AND DIMENSIONS

Control Unit	232 x 148 x 120 mm / 6.63 kg
	9.13 x 5.83 x 4.72 in / 14.61 lb
Package	495 x 415 x 395 mm / 10.79 kg
	19.49 x 16.34 x 15.55 in / 23.79 lb