

HM 2600 E

Powerful. Tough. Robust.

Technical Specifications

Power supply: 120 V, 60 Hz
Output: 1750 W
Temperature: 120 - 1150° F
Temperature setting: 9 temperature settings
Thermal cutout: Yes
Airflow rate: 13 cfm (+/- 0.5 cfm)

Features: Easy thumbnail dial, plug-in heating element, ergonomic grip, fine dust filter, field changeable power cord, restart protection.

Applications: Suitable for construction site use
Motor: Brushless
Motor life: 10,000 hours
Heating element: Ceramic heating element

Weight: 1.85 lbs.
Dimensions: 14.10" x 3.75" x 3.85"
(L x W x D)
Warranty: 1 year



UPC Code	Product No.
018139004349	110100434

HM 2600 E without restart protection

Powerful. Tough. Robust. Safe.

Technical Specifications

Power supply: 120 V, 60 Hz
Output: 1750 W
Temperature: 120 - 1150° F
Temperature setting: 9 temperature settings
Thermal cutout: Yes
Airflow rate: 13 cfm (+/- 0.5 cfm)

Features: Easy thumbnail dial, plug-in heating element, ergonomic grip, fine dust filter, field changeable power cord, without restart protection (automatically turns on and returns to last temperature / airflow settings upon regain of power).

Applications: Ideal for manufacturing
Motor: Brushless
Motor life: 10,000 hours
Heating element: Ceramic heating element

Weight: 1.85 lbs.
Dimensions: 14.10" x 3.75" x 3.85"
(L x W x D)
Warranty: 1 year



UPC Code	Product No.
018139092322	110109232