

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Permatex® Anaerobic Flange Sealant - 50 ml

Product Code: 51531 51531 Stock No.: Manufacturer Name: Permatex, Inc.

10 Columbus Blvd. Address: Hartford, CT 06106

USA

General Phone Number:

1-87-Permatex, (877) 376-2839 800-255-3924

Emergency Phone Number:

CHEMTREC:

For emergencies in the US, call CHEMTREC: 800-424-

9300

MSDS Creation Date: December 27, 2008 MSDS Revision Date: December 30, 2012

(M)SDS Format:

HMIS	
Health Hazard	2
Fire Hazard	1
Reactivity	
Personal	1
Protection	

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Methacry ate	868-77-9	<5 by weight
Polyurethane methacrylate resin	Mixture	50 - 60 by weight
Polyethylene glycol dimethacrylate	25852-47-5	10 - 30 by weight
Acrylic acid	79-10-7	<5 by weight
Amorphous silicon dioxide	67762-90-7	<10 by weight
Cumene hydroperoxide	80-15-9	<3 by weight

SECTION 3: HAZARDS IDENTIFICATION

Emergency Overview: CAUTION! Harmful. Irritant. Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eve: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.

Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. May cause skin sensitization, an allergic reaction, which Skin:

becomes evident on reexposure to this materia

Inhalation: Respiratory tract irritant. High concentration may cause dizziness,

headache, and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Individuals with pre-existing skin disorders, asthma, allergies or known Aggravation of Pre-Existing Conditions sensitization may be more susceptible to the effects of this product.

SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20

minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Skin Contact:

Get medical attention if irritation develops or persists

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial

respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control

center immediately. Never give anything by mouth to an unconscious

Flash Point: >200 °F (>93.3°C)

Flash Point Method: Tag closed cup (TCC)

Auto Ignition Temperature: Not determined.

Lower Flammable/Explosive

Lim it:

Not determined.

Upper Flammable/Explosive

Lim it:

Not determined.

Fire Fighting Instructions:

Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire

run-off water.

Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving

this material.

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear. Protective Equipment:

Unusual Fire Hazards: None known.

NFPA Ratings:

NFPA Health:

NFPA Flammability:

NFPA Reactivity:

NFPA Other:

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Evacuate area and keep unnecessary and unprotected personnel from

entering the spill area.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Spill Cleanup Measures: Absorb spill with inert material (e,g., dry sand or earth), then place in a

chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue

Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.

Methods for containment: Maintain good ventilation. Take up with an inert absorbent. Store in a

closed waste container until disposal.

Methods for cleanup: Maintain good ventilation. Take up with an inert absorbent. Store in a

closed waste container until disposal.

Other Precautions: Pump or shovel to storage/salvage vessels. Add inhibitor to prevent

polymerization.

SECTION 7: HANDLING and STORAGE

Skin Protection Description:

Respiratory Protection:

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Storage: Store in a cool, dry, well ventilated area away from sources of heat and

incompatible materials. Keep container tightly closed when not in use.

Store below 100 °F

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting

operations and to protect against dust during sanding/grinding of cured

product.

Hygiene Practices: Wash thoroughly after handling.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne

levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and

maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by

 $29\ \text{CFR}\ 1910.133$, OSHA eye and face protection regulation, or the European standard EN 166.

Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability

data.

A NIOSH approved air-purifying respirator with an organic vapor Product: Permatex® Anaerobic Flange Sealant - 50 ml | Manufacturer: | Revision:12/30/2012, Version:0 pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circum stances where air purifying respirators may not provide adequate

Other Protective: Facilities storing or utilizing this material should be equipped with an

eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Acrylic acid:

Guideline ACGIH: 2 ppm Skin: Yes

TLV-TWA: 2 ppm

Notes: Only established PEL and TLV values for the ingredients are listed.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Gel

Color: Purple

Odor: Sharp Irritating Boiling Point: >150°F (74.4°C) Melting Point: Not determined. Specific Gravity: 1.1 @ 80 °F

Solubility: Sliaht

Vapor Density: Heavier than air. Vapor Pressure: <5 mmHg @68°F Evaporation Rate: Not determined. Evaporation Point: Not determined. pH: Not determined.

Molecular Formula: Mix ture Molecular Weight: Mix ture

Flash Point: >200 °F (>93.3°C) Flash Point Method: Tag closed cup (TCC) Auto Ignition Temperature: Not determined. VOC Content: Not determined.

SECTION 10: STABILITY and REACTIVITY

Chemica | Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Polymerization may occur under certain conditions.

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Oxygen-free atmospheres or inert

gas blanketing. Freezing conditions. Material can soften paint and

rubber.

Incompatible Materials: Oxidizing agents (eg peroxides, nitrates), reducing agents, acids,

bases, azo-compounds, catalytic metals (eg copper, iron), halogens.

Free radical initiators. Oxygen scavengers.

SECTION 11: TOXICOLOGICAL INFORMATION

Methacrylate:

OZ4725000 RTECS Number:

Ingestion: Oral - Rat LD50: 5050 mg/kg [Behavioral - Coma]

Oral - Mouse LD50: 3275 mg/kg [Behavioral - Coma]

Acrylic acid:

RTECS Number: AS4375000

Eye: Eye - Rabbit Standard Draize test.: 1 mg

Eye - Rabbit Standard Draize test.: 250 ug/24H

Skin: Administration onto the skin - Rabbit : 280 uL/kg [Details of toxic

Administration onto the skiii - Rabbit : 280 uL/kg [Petalis of toxic effects not reported other than lethal dose value]
Administration onto the skiin - Rabbit : 640 mg/kg [Cardiac - Cardiomegaly Lungs, Thorax, or Respiration - Acute pimonary edema Skiin and Appendages - Corrosive (After topical exposure)]
Administration onto the skiin - Guinea pig : 5 pph/12W (Intermittent)

[Skin and Appendages - Cutaneous sensitization, experimental (After topical exposure)]

Administration onto the skin - Rabbit : 500 mg

Product: Permatex® Anaerobic Flange Sealant – 50 ml | Manufacturer: | Revison:12/30/2012, Version:0

Leukemia]

Administration onto the skin - Mouse : 37440 mg/kg/78W (Intermittent) [Tumorigenic - equivocal Tumorigenic agent by RTECS

criteria Skin and Appendages - Tumors]

Inhalation:

Inhalation - Mouse LC50: 5300 mg/m3/2H [Details of toxic effects not

reported other than lethal dose value]

Ingestion: Oral - Rat LD50: 33500 ug/kg [Details of toxic effects not reported

other than lethal dose value]
Oral - Mouse LD50: 2400 mg/kg [Tumorigenic - Active as anti-cancer

agent]

Amorphous silicon dioxide :

VW 3234375 RTECS Number:

Cumene hydroperoxide:

RTECS Number: MX2450000

Eye: Eye - Rabbit Standard Draize test.: 1 mg

Eye - Rabbit Standard Draize test.: 70%

Skin: Administration onto the skin - Rat : 500 mg/kg [Behavioral Convulsions or effect on seizure threshold Kidney/Ureter/Bladder -

Hematuria 1

Administration onto the skin - Rabbit : 1200 mg/kg [Cardiac - Pulse rate increase, without fall in BP Blood - changes in erythrocyte (RBC) count Nutritional and Gross Metabolic - Body temperature decrease] Administration onto the skin - Mouse : 490 mg/kg [Details of toxic effects not reported other than lethal dose value]

Administration onto the skin - Mouse : 1200 mg/kg [Biochemical -Enzyme inhibition, induction, or change in blood or tissue levels -Catalases Biochemical - Enzyme inhibition, induction, or change in blood or tissue levels - Other oxidoreductases Biochemical - Enzyme inhibition, induction, or change in blood or tissue levels - Other transferases]

Administration onto the skin - Rat : 250 mg/kg [Vascular - Structural changes in vessels Biochemical - Metabolism (Intermediary) - Effect on

inflammation or mediation of inflammation]

Administration onto the skin - Mouse : 300 mg/kg [Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of

inflam mation]

Administration onto the skin - Mouse : 2012 mg/kg/2W (Intermittent) [Skin and Appendages - Tumors Biochemical - Metabolism (Intermediary) - Other proteins]
Administration onto the skin - Mouse : 20.1 gm/kg/20W (Intermittent)

[Skin and Appendages - Tumors Tumorigenic - Facilitates action of known carcinogen Biochemica| - Metabolism (Intermediary) - Effect on inflammation or mediation of inflammation]

Administration onto the skin - Mouse : 30442 ug/kg/4W (Intermittent) [Biochemical - Metabolism (Intermediary) - Effect on inflammation or

mediation of inflammation]

Administration onto the skin - Mouse : 100 mg/kg Administration onto the skin - Rabbit : 500 mg Administration onto the skin - Rabbit : 500 mg Administration onto the skin - Mouse : 18000 ug/kg/18W

(Intermittent) [Tumorigenic - carcinogenic by RTECS criteria Skin and Appendages - Tumors Tumorigenic - Facilitates action of known

carcinogen]

Inhalation - Rat LC50: 220 ppm/4H [Lungs, Thorax, or Respiration -Inhalation:

Dyspnea] Inhalation - Mouse LC50: 200 ppm/4H [Lungs, Thorax, or Respiration -

Dyspnea]

Oral - Rat LD50: 382 mg/kg [Kidney/Ureter/Bladder - Hematuria] Oral - Mouse LD50: 342 mg/kg [Details of toxic effects not reported Ingestion:

other than lethal dose value]
Oral - Rat LD50: 800 mg/kg [Details of toxic effects not reported other

than lethal dose value]

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the

EPA and/or state and local guidelines.

RCRA Number: Not determined.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated DOT UN Number: Not applicable. DOT Hazard Class: Not applicable. IATA Shipping Name: Non regulated. IATA UN Number: Not applicable. IATA Hazard Class: Not applicable.

SECTION 15: REGULATORY INFORMATION

Section 313:

The following component(s) is listed as a SARA Section 313 Toxic Chemical. SARA 313 Information ACRYLIC ACID, DIMETHYLBENZYL

HYDROPEROXIDE

Methacrylate:

TSCA Inventory Status: Listed Canada DSL: Listed Polyethylene glycol dimethacrylate:

TSCA Inventory Status: Listed Canada DSL: Listed

Acrylic acid:

TSCA Inventory Status: Listed

EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed SARA:

Chemical.

New Jersey: Listed: NJ Hazardous List; Substance Number: 0023

Listed: Massachusetts Oil and Hazardous List Massachusetts:

Pennsylvania: Listed Canada DSL: Listed

Amorphous silicon dioxide:

TSCA Inventory Status: Listed Canada DSL: Listed

<u>Cumene hydroperoxide</u>:

TSCA Inventory Status: Listed

EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed SARA:

New Jersey: Listed: NJ Hazardous List; Substance Number: 0543

Massachusetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed Canada DSL: Listed

WHMIS Hazard Class(es): D2B Canadian Regulations.

All components of this product are on the Canadian Domestic Substances

SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: December 27, 2008 December 30, 2012 MSDS Revision Date: MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our

knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a

controlled environment.

Copyright@ 1996-2013 Actio Corporation. All Rights Reserved.